

Soft PVC hose Yellow transparent version or Crystal with hard PVC spiral.

Suitable for suction and delivery of food liquids.



Flexibility



Crushing resistance



Abrasion resistance



Chemical resistance

Chemical Resistance Chart

Temperature range

-5°C +60°C



Agriculture



Industry



Home



Building



Food & beverage

Suitable for contact with food and food liquids Simulant A.B.C and alcoholic liquids up to 20% in compliance with Regulation (EC) No. 1935/2004, Regulation (EC) No. 2023/2006 and Regulation (EU) No. 10/2011 and its successive amendments.

Phthalate FREE. 

Part.no.	ID inch	ID mm	OD mm	Weight g/m	Bend radius mm	Workpress bar	Burstpress bar	Vacuum mH2O	Coillenght mt	Pallet mt	Dimension pallet cm
587J.....	1\2	13	17,0	100	60	6	18	7	50	3000	80x120
587J.....	5\8	16	21,0	130	75	6	18	7	50	3000	80x120
587J.....		18	23,0	180	80	6	18	7	50	2500	80x120
587J1320		20	26,0	230	90	6	18	7	50	2500	80x120
587J1330	1	25	31,5	280	115	6	18	7	50	1200	80x120
587J1340		30	37,0	350	135	5	15	7	50	1000	80x120
587J1350	1 1\4	32	39,0	380	145	5	15	7	50	1000	80x120
587J1360		35	42,0	425	160	5	15	7	50	500	80x120
587J1370	1 1\2	38	45,5	470	170	5	15	7	50	300	80x120
587J1380		40	47,5	510	180	5	15	7	50	300	80x120
587J1390	1 3\4	45	53,0	640	205	5	15	7	50	300	80x120
587J1400		50	58,5	760	225	5	15	7	50	300	80x120
587J1410	2	51	59,5	770	230	5	15	7	50	300	80x120
587J1420		55	64,0	830	250	4	12	7	50	300	110x130
587J1430		60	69,5	900	270	4	12	7	50	250	110x130
587J1440	2 1\2	63	72,5	950	285	4	12	7	50	250	110x130
587J1450		65	75,0	1000	295	4	12	7	50	250	110x130
587J1460		70	80,0	1125	315	4	12	7	50	250	110x130
587J1470		75	85,0	1290	340	4	12	7	30	240	110x130
587J1480	3	76	86,0	1300	345	4	12	7	30	240	110x130
587J1490		80	91,0	1450	360	3	9	7	30	240	110x130
587J1500	3 1\2	90	101,5	1725	405	3	9	7	30	210	110x130
587J1510		100	112,0	2000	450	3	9	7	30	180	110x130
587J1520		110	123,0	2300	495	2	6	7	30	180	110x130
587J1530		120	133,0	2630	540	2	6	7	30	180	110x130
587J1540		125	138,0	2785	565	2	6	7	30	120	110x130
587J1550	5	127	140,0	2860	575	2	6	7	30	120	110x130
587J1560		130	144,0	2940	585	2	6	7	30	120	110x130
587J1570		140	154,0	3250	630	2	6	7	30	120	110x130
587J1580		150	165,0	3900	675	2	6	7	20	100	110x130
587J1590	6	152	167,0	4000	685	2	6	7	20	100	110x130
587J1600		160	176,0	5000	720	-	-	-	20	80	110x130
587J1610		180	197,0	5600	810	-	-	-	20	60	110x130
587J1620		200	218,0	6200	900	-	-	-	20	60	110x130

NOTES:
 CHEMICAL RESISTANCE CHART available on TP REFLEX web site.
 TEMPERATURE RANGE based on qualified literature; material datasheet or product tests. WORKING/BURST PRESSURE based on tests performed with water at temperature of 23±2 °C.
 DIMENSIONS AND PERFORMANCES referred to a temperature of 23±2 °C; different temperature as well as handling, storage, aging or application conditions can lead to different values.
 TOLERANCE: from 12 mm to 20 mm: ± 0.3 mm | from 22 mm to 50 mm: ± 0.5 mm | from 51 mm to 100 mm: ± 1.0 mm | from 102 mm to 150 mm: ± 1.5 mm from 152 mm to 200 mm: ± 2.0 mm other values: ±5%
 TIGHTNESS of hose to be tested after assembly of fittings; the test should be performed in safe conditions. TP REFLEX sales department is at disposal to evaluate requests concerning product application.
 TP REFLEX has the right to modify the elements of this catalogue and declines any responsibility for unlike applications/misapplication of its products.